

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An infusion set, comprising:

a base for providing an infusion path, said base having a first surface that faces a skin surface of a user when said base is supported on said skin surface and when said infusion set is used to pass fluids to said user;

a cannula connected to and extending away from the base;

a connector removably attachable to the base; and

a tubing affixed to the connector,

wherein the connector is ~~limitedly~~ rotatable on the base, to more than 5 degrees and limited to less than 360 degrees around an axis that is substantially perpendicular to said first surface of said base, when the connector is removably attached to the base, and

wherein a contiguous passage for passing fluids is formed from the tubing to the cannula when the connector is removably attached to the base.

2. (Original) The infusion set of Claim 1, wherein the base comprises at least one barrier extending away from a surface of the base.

3. (Original) The infusion set of Claim 2, wherein the connector comprises at least one stop extending away from a surface of the connector.

4. (Original) The infusion set of Claim 3, wherein the at least one barrier is disposed on the base so that it restricts the movement of the at least one stop when the connector is rotated about the base.

5. (Original) The infusion set of Claim 1, wherein the connector is limited to a rotation of 60 degrees when the connector is removably attached to the base.

6. (Original) The infusion set of Claim 1, wherein the connector is limited to a rotation of 90 degrees when the connector is removably attached to the base.

7. (Original) The infusion set of Claim 1, wherein the connector is limited to a rotation of 120 degrees when the connector is removably attached to the base.

8. (Original) The infusion set of Claim 1, further comprising:

a hub removably affixable to the base;

a needle attached to the hub, the needle being removably insertable into the cannula; and

a cover for covering the needle.

9. (Original) The infusion set of Claim 8, further comprising an adhesive pad affixed to the base, wherein the cannula extends through the adhesive pad.

10. (Currently Amended) A method for using an infusion set, comprising:

positioning a base on an infusion site of a user, said base having a first surface that faces a skin surface of said user when said base is supported on said skin surface and positioned on said infusion site;

positioning a connector onto the base, the connector including a delivery tubing; and

adjusting a position of the delivery tubing,

wherein adjusting the position of the delivery tubing is ~~limited to a range of~~ allowed to more than 5 degrees and limited to less than 360 degrees in a rotational direction around an axis that is substantially perpendicular to said first surface of said base.

11. (Original) The method of Claim 10, wherein adjusting the position of the delivery tubing is limited to a range of 120 degrees.

12. (Original) The method of Claim 10, wherein adjusting the position of the delivery tubing is limited to a range of 90 degrees.

13. (Original) The method of Claim 10, wherein adjusting the position of the delivery tubing is limited to a range of 60 degrees.

14. (Original) The method of Claim 10, wherein adjusting the position of the delivery tubing is limited to a range of 30 degrees.

15. (Currently Amended) A subcutaneous infusion set, comprising:

a base portion having a receiving area, said base portion having a first surface that faces a skin surface of a user when said base portion is supported on said skin surface and when said subcutaneous infusion set is used to pass fluids to said user;

a cannula affixed to the base portion;

a connector portion for removable attachment to the base, the connector being received in the receiving area of the base portion; and

a tubing affixed to the connector portion,

wherein an angular movement of the connector portion is allowed to more than 5 degrees and is restricted by the base portion to less than 360 degrees around an axis that is substantially perpendicular to said first surface of said base portion, and

wherein a fluid passes from the tubing to the cannula when the connector is attached to the base.

16. (Original) The infusion set of Claim 15, wherein the base portion comprises at least one first member extending away from a surface of the base portion.

17. (Original) The infusion set of Claim 16, wherein the connector portion comprises at least one second member extending away from a surface of the connector portion.

18. (Original) The infusion set of Claim 17, wherein the at least one first member is disposed on the base portion so that it restricts the movement of the at least one second member when the connector portion is rotated about the base portion.

19. (Original) The infusion set of Claim 15, wherein the connector portion is limited to a rotation of 60 degrees when the connector is removably attached to the base portion.

20. (Original) The infusion set of Claim 15, wherein the connector portion is limited to a rotation of 90 degrees when the connector is removably attached to the base portion.

21. (Original) The infusion set of Claim 15, wherein the connector portion is limited to a rotation of 120 degrees when the connector is removably attached to the base portion.

22. (Original) The infusion set of Claim 15, further comprising:

- a hub removably affixable to the base portion;

- a needle attached to the hub, the needle being removably insertable into the cannula; and

- a cover for covering the needle.

23. (Original) The infusion set of Claim 22, further comprising an adhesive pad affixed to the base, wherein the cannula extends through the adhesive pad.

24. (Currently Amended) An infusion set, comprising:

means for positioning a base on an infusion site of a user, said base having a first surface that faces a skin surface of said user when said base is supported on said skin surface and positioned on said infusion site;

means for positioning a connector onto the base, the connector including a delivery tubing; and

means for adjusting a position of the delivery tubing,

wherein adjusting the position of the delivery tubing is ~~limited to a range of~~ allowed to more than 5 degrees and limited to less than 360 degrees in a rotational direction around an axis that is substantially perpendicular to said first surface of said base.

25. (Currently Amended) The infusion set of claim 24, wherein ~~the means for adjusting the position of the delivery tubing is further limited to no rotation~~ allowed to more than 10 degrees and limited to less than 360 degrees in said rotational direction around said axis.

26. (Currently Amended) The infusion set of claim 1, wherein ~~the limited rotation of the connector is further limited to no rotation~~ rotatable on the base to more than 10 degrees and limited to less than 360 degrees around said axis.

27. (Currently Amended) The method of claim 10, wherein ~~the step of said adjusting the position of the connector~~ delivery tubing is further limited to no rotation is allowed to more than 10 degrees and limited to less than 360 degrees in said rotational direction around said axis.

28. (Currently Amended) The infusion set of claim 15, wherein the angular movement of the connector portion is ~~further limited to no rotation~~ allowed to more than 10 degrees around said axis.

29. (New) An infusion set, comprising:

- a base for providing an infusion path;
- a cannula connected to and extending away from the base;
- a connector removably attachable to the base in any one of at least two different connection positions, said connector being rotatable on said base, each connection position of said at least two different connection positions allowing for different possible relative orientations of said connector with respect to said base when said connector is rotated on said base; and
- a tubing affixed to the connector.

30. (New) The infusion set of claim 29,

wherein said base comprises at least two barriers that are spaced apart from each other around a circumference of said base; and

wherein said connector comprises a stop for preventing further rotation of said connector in a particular rotational direction on said base when said stop contacts one of said at least two barriers of said base.

31. (New) The infusion set of claim 30,

wherein a plurality of intervals around said circumference of said base are defined between barriers of said at least two barriers; and

wherein each of the at least two different connection positions provides for placing the stop of the connector within a respectively different interval of said plurality of intervals than all other connection positions of said at least two different connection positions.

32. (New) The infusion set of claim 31,

wherein a first interval of said plurality of intervals is limited to less than 120 degrees around said circumference of said base.

33. (New) The infusion set of claim 31,

wherein said connector includes a plurality of stops, each stop of said plurality of stops being located in a respectively different interval of said plurality of intervals when said connector is attached to said base.